



ACTIVE TRANSPONDERS

The transponders are detected by a wire timing loop. They provide highest accuracy and 100% detection rate at a low power consumption. The four models are tuned to different application scenarios, but can be used in the same race.

ActiveBasic V3



ActivePro V3



ActivePro V3 Performance



MotorKart V3



Warranty* / Battery Lifetime

	ActiveBasic V3	ActivePro V3	ActivePro V3 Performance	MotorKart V3
Years	4 years	5 years	3.5 years	3.5 years
Passings	50	100	50	300
Tracking fast / slow	-	400/1000 days	150/300 days	150/300 days

Please note: The battery cannot be replaced.

Detection

	ActiveBasic V3	ActivePro V3	ActivePro V3 Performance	MotorKart V3
Accuracy	0.2 s	0.004 s	0.004 s	0.004 s
Max. speed	60 km/h	120 km/h	150 km/h	120 km/h
Resolution**	0.001 s	0.001 s	0.001 s	0.001 s
2.4 GHz backup	dual	dual	quad	dual
Exit passing precision	170 ms	100 ms	50 ms	170 ms
Reaction time	500 ms	250 ms	125 ms	125 ms
Loop Antenna	2D	3D	3D	3D
Prewarn	-	-	✓	-
Detection height	2 m	2 m	2m	0.5m

Tracking

	ActiveBasic V3	ActivePro V3	ActivePro V3 Performance	MotorKart V3
Max. time between Track Boxes	-	5 h	5 h	5 h
Max. time between Loops	-	25 h	25 h	25 h
Typical track ping range	-	50 m	200 m	50 m
Activation	-	Loop ID 8 + Channel ID 8	Loop ID 8 + Channel ID 8	Management Box
Adaptive track ping intervals	-	5 s / 2 s / 1 s	1 s / 0.5 s	1 s / 0.5 s

Store Mode

	ActiveBasic V3	ActivePro V3	ActivePro V3 Performance	MotorKart V3
Max. passings stored	-	64	128	128
Max. store time	-	12 h	24 h	12 h
Store Mode precision	Temperature compensated +-5ppm			
Temperature	-25°C - 70°C			

Features

	ActiveBasic V3	ActivePro V3	ActivePro V3 Performance	MotorKart V3
Extra transponder code	✓	✓	✓	✓
Adaptive noise avoidance	✓	✓	-	-
Key-value store	✓	✓	✓	✓
Deep sleep mode	✓	✓	✓	✓